

Construction Resources



AQUAMARIJN TECHNICAL SHEET A10

BALIM OIL & WAX BALSAM

Uses *Aquamarijn Balim* oil/wax balsam is a primary and finishing treatment in one tin for all untreated interior wood and cork.

Properties: Produces very little change in base colour. Water dilutable, 100% solvent free. Easy to apply, dries exceptionally quickly.

Colours Clear.

Containers 0.75 and 2.5 litre tins.

Coverage 0.75 litre tin: 8 - 15 m² depending on absorbency of the surface.
2.5 litre tin: 25 - 45 m² depending on absorbency of the surface.

Preparation Surfaces should be clean and free from grease and dust.

Application One coat is usually enough, though for best results finish with *Aquamarijn Crelim Liquid Hard Conditioning Wax* treatment. The wax/oil should be spread and rubbed in evenly across the floor using either a cotton cloth or, for larger areas, a rotary machine with a beige pad. Leave the wax/oil for approx. 40 minutes to allow the water to evaporate then buff surface with a dry cotton cloth or a rotary machine with a suitable fine grade pad.

Use With *Aquamarijn Crelim Liquid Hard Conditioning Wax.*
Holzweg Floor Cream Cleaner and Floor Maintainer.
Holzweg Floor Soap Heavy Duty Cleaner.

Drying times The surface is useable after 4 hours, though treat with care.

Maintenance To help maintain the wax finish, clean floors using *Holzweg Floor Cream* which contains carnauba wax. To bare areas re-apply *Aquamarijn Balim*, followed by one coat of *Aquamarijn Crelim* according to instructions on technical sheet A13.

Storage Store sealed in a cool dry, but frost-free place. Limited shelf life once opened.

Ingredients Linseed oil and wood oil emulsified in water, carnauba wax, bees wax, emulsifying agent, water, synthetic preservative (approved for use in food packaging by the BGA and FDA**).

Safety None.

General precautionary measures

** BGA, the German Federal Health Office and the FDA is the US Food and Drugs Administration

Avoid contact with the eyes. Do not throw any waste down the drains. Always try to dispose of waste at a registered disposal dump. Paints etc. should always be kept out of the reach of children and animals.

Technical details

All Aquamarijn products are divided into categories depending on the degree of natural materials used in the manufacturing process. Class 1 is 99% natural, class 2 is 95%, class 3 is 90% and class 4 is 70%, the classification number appears on the front of each label.

Aquamarijn Balim is Class 2.

Binding agent	Linseed oil, carnauba wax and bees wax emulsified in water.
Thinner	Water
Transport code	ADR none
Danger code	N/A
Flash point	None
Solids by volume	23-27 weight %, 23 - 27 vol.%
Weight (approx.)	0.98 – 1.02 kg/L
Viscosity	Thick fluid at 18 °C
Gloss degree	25 - 35 (satin gloss)
Elasticity	
Remarks	

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued on August 1999 and may be superseded by later editions.

© CONSTRUCTION RESOURCES 1999
16 Great Guildford Street, SE1 0HS
Tel: 0207 450 2211. Fax: 0207 450 2212.
Email: info@ecoconstruct.com
www.ecoconstruct.com