

Construction Resources



AQUAMARIJN TECHNICAL SHEET A14

CORCOL – SOLVENT FREE FLOOR OIL

Uses Professional solvent free nourishing oil for untreated cork and absorbent wooden floors of pine or beech, etc. indoors only.

Properties 100% solvent free. Contains a mixture of linseed and wood oil. Impregnating, penetrating and protective. Dirt and water resistant.

Containers 1 litre and 5 litre tins.

Coverage 1 litre will cover approximately 15 m² depending on absorbency of wood treated.

Colours Clear, gives the timber a slightly darker honey tone.

VOC Level 0 %

Preparation Ensure surface is sound, dry, clean, grease / dust free and well sanded (do not sand cork).

Application **Shake the Corcol well. A) Spreading:** Sparingly apply with cloth or buffer. if necessary apply again on strong absorbing wood species. Allow 20 - 60 minutes for it to absorb. **B) Rubbing in:** Rub with a sound pad, preferably with a rotary machine. Remove the surplus. **C) Rubbing Dry:** Rub completely dry using a rotary machine with a fine grade pad - green or white and cotton rag. If required finish with *Aquamarijn Crelim Wax* after at least 48 hours.

Note - insufficient rubbing will leave sticky remains.

Cork: Low quality cork tiles, because of the high proportion of sawdust used in their manufacture, or cork tiles that have epoxy resin as a binder may not take the treatment well and may take a long time to dry. It is strongly recommend that a small sample area is tested before full treatment.

Use with *Aquamarijn Crelim Wax*
Holzweg Floor Soap (maintenance)

Drying times Useable with care after 24 – 48 hours at 20°C. **Water resistant** after 7 -14 days.

Maintenance To help maintain the oil finish, clean floor using *Holzweg Floor Soap*. To bare areas re-apply *Corcol*.

General Tips **Maintain floors with a cleaner** containing natural oils such as *Holzweg Floor Soap* that cleans and nourishes in one.

Use walk-off mats at all exterior doors to prevent dirt, grit and sand from getting into the building. Throw rugs or small sections of bordered natural carpet/sisal inside entrances are also helpful. Be sure to use rugs that allow the floor to

“breathe” (see CR Interiors carpet technical sheet). Avoid rugs with rubber backing or other non-ventilating material. Dirt and grit are a floor’s worst enemy. **Certain chemicals in wood oxidize** in strong light causing the wood to change colour. To avoid an uneven appearance, move area rugs regularly and drape or shade windows that allow extended periods of direct sunlight on the floor. **Put soft, protective glides on the legs of all your furniture.** This will allow the furniture to be moved easily without scuffing or scratching the floor. Be sure to clean the glides regularly as dirt may become embedded in them. It is also important to make sure that the glides are in good repair.

Storage Store sealed in a cool dry, but frost-free place.

Ingredients Linseed oil and wood oil, essential oils, cobalt drier.

Safety None. Fully biodegradable.

General precautionary measures

Avoid contact with skin and eyes. Always ventilate when painting: aids the drying process. Do not throw any waste down the drains, always try to dispose of waste at a registered disposal dump. Paints etc. should always be kept out of the reach of children and animals. Always allow rags, soaked in linseed oil paint, to dry unfolded to avoid self ignition. Limited shelf life once opened.

Technical details All Aquamarijn products are divided into categories depending on the degree of natural materials used in the manufacturing process. Class 1 is 99% natural, class 2 is 95%, class 3 is 90% and class 4 is 70%, the classification number appears on the front of each label.

Aquamarijn Corcol is Class 1.

Binding agent	Linseed oil and wood oil
Thinner	none
Transport code	ADR none
Danger code	N/A
Viscosity	Thick fluid at 18 °C
Gloss degree	N/A
Elasticity	N/A

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued on 18 November 2005 and may be superseded by later editions.

© CONSTRUCTION RESOURCES 2003
16 Great Guildford Street, SE1 0HS

Tel: 0207 450 2211. Fax: 0207 450 2212.

info@ecoconstruct.com

www.ecoconstruct.com