

Construction Resources



HOLZWEG / VOLVOX TECHNICAL SHEET H12

WHITE UNDERCOAT 2-3703

- Uses** *Holzweg/Volvox White Undercoat* is used prior to gloss or satin finishing coats such as *Holzweg Eggshell*, *Aquamarijn Satilin Eggshell*, *Holzweg External Gloss* or *Aquamarijn Toplin Gloss* on interior and exterior wood and metal. It is ideal for use where a natural product is necessary but drying times are critical.
- Properties** *Holzweg/Volvox White Undercoat* is an opaque, matt white undercoat used to give subsequent coats a firm and long lasting base. It spreads well and is easy to use. Quick-drying and microporous. Soya oil based.
- Colour** White, matt finish.
- Containers** Supplied in 0.75 litre, 2.5 litre and 10 litre containers.
- Coverage** 1 litre will cover approximately 10-12 m² on a smooth wood surface of average absorbency.
- Preparation** The surface should be smooth, clean, grease-free, dry, and in the case of wood, absorbent. Previously-primed surfaces must be sanded down gently before painting using fine grade sandpaper.
- Application** Stir *Holzweg/Volvox White Undercoat* thoroughly before use. Apply one to two coats evenly, depending on original colour and condition of the surface. When dry, gently rub down to remove any surface blemishes.
- Drying time** Dust-dry after 1¹/₂ hours; touch-dry after 3 hours; re-coatable after 8 – 10 hours. Allow 24 hours before sanding and applying finishing coat.
- Storage** Store tightly sealed, in a cool but frost-free place. Storing the tin upside-down will help prevent a skin forming on the paint - but be sure it is well sealed.
- Ingredients** Soya alkyd; soya lecithin; sheet silicates; titanium dioxide; calcium carbonate; silicon dioxide; isoparaffin; lead-free dryers; anti-skinning agent.
- Safety** **This product is flammable and easily ignited!** While working do not smoke and use no naked flame. During and after application keep room well ventilated. Paint-soaked cloths should not be left lying around as there is a possibility of self-ignition. Spread cloths out to dry outdoors, completely unfolded, or store them away in a sealed container. Keep paint tins sealed and out of the reach of children. All ingredients are biodegradable, but leftover paint should not be put down the drain.
- Risk class** Inflammable! GGVS Class 3.3. UN number 126.3

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued in August 2005 and may be superseded by later editions.

© **CONSTRUCTION RESOURCES** 1999
16 Great Guildford Street, SE1 0HS
Tel: 0207 450 2211. Fax: 0207 450 2212.
Email info@ecoconstruct.com