

Construction Resources



HOLZWEG TECHNICAL SHEET H22

GARDEN FENCE PAINT

- Uses** *Holzweg Garden Fence Paint* is designed to provide exterior wood protection. Suitable for all exterior timbers, especially garden fences, gateposts, etc.
- Properties** *Holzweg Garden Fence Paint* is oil based, water resistant and weather proof. It penetrates well, nourishing the timber and allowing it to 'breathe'. It contains linseed oil.
- Colours** Supplied in a rich deep brown.
- Containers** 2.5 and 10 litre tins, samples are available in 125 ml.
- Coverage** 1 litre will cover about 10 m² depending on the absorbency of the timber.
- Preparation** The surface must be clean, grease free, absorbent and dry.
- Application** Stir the contents well before use. On untreated timber it is advisable to apply two coats, using either a brush or roller. Tools can be cleaned with *Holzweg Balsamic Turpentine*.
- Drying times** Depending on local conditions, state of timber and weather etc, drying time is approximately between 8 – 10 hours.
- Storage** Tightly sealed, cool but frost free.
- Safety** This product is inflammable. While working observe standard safety practice, do not smoke and use no naked flames. Paint soaked rags should not be left lying around, they should be spread out to dry outdoors. Keep contents away from children. Although the ingredients are biodegradable, they should not be poured down the drains. They can be disposed of on the compost heap.
- Risk class** Inflammable! GGVS Class 3.3 UN number 126.3
- Ingredients** Treated linseed oil, wood oil, natural pigments, orange terpenes, balsamic turpentine, lead free drying agents.

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued on August 1999 and may be superseded by later editions.

© CONSTRUCTION RESOURCES 1999
16 Great Guildford Street, SE1 0HS
Tel: 0207 450 2211. Fax: 0207 450 2212.
Email: info@ecoconstruct.com