

Construction Resources



HOLZWEG TECHNICAL SHEET H29

FLOOR / SURFACE SOAP

- Uses** *Holzweg Floor Soap* is a traditional recipe from Scandinavia for a tough soap used in cleaning and maintaining oiled and/or waxed wood, stone or cork floors or other surfaces. Also known as *Holzweg Wood Soap*.
- Properties** Removes dirt, leaving a thin protective film.
- Container** 1 litre and 5 litre bottles.
- Coverage** Strength required depends on the condition of the floor: 1 litre of *Holzweg Floor Soap* will make up between 40 to 50 litres when mixed with warm water.
- Preparation** Mix one to two capfuls of *Holzweg Floor Soap* to one litre of warm water.
- Application** Use as for normal cleaning solutions, i.e. with mops or other cleaning tools straight from bucket. Leave the surface as dry as possible after cleaning it. Do not leave large areas of standing water on the surface. The floor can be polished once dry. Buckets, mops and cloths can be cleaned with warm water.
- Drying times** The surface is polishable after approximately one hour.
- Storage** Keep container sealed, cool but frost free and out of the reach of children.
- Risk class** None
- Ingredients** Plant oil soaps, water, linseed oil, wood oil.

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued in March 2002 and may be superseded by later editions.

© CONSTRUCTION RESOURCES 1999
16 Great Guildford Street, SE1 0HS
Tel: 0207 450 2211. Fax: 0207 450 2212.
Email: info@ecoconstruct.com
Web Page: www.ecoconstruct.com