

# Construction Resources



## HOLZWEG TECHNICAL SHEET H30

---

### WAX FINISH

- Uses** *Holzweg Wax Finish* is a wax emulsion for the finishing treatment of oiled surfaces. *Holzweg Wax Finish* can also be used as a cleaning and maintaining fluid for waxed surfaces. Used for the protection and maintenance of wooden, stone, cork and linoleum floors indoors.
- Properties** *Holzweg Wax Finish* is an emulsion of Carnauba wax, alcohol ester and water which is very stable, water repellent and polishable.
- Container** 1 litre and 5 litre.
- Coverage** 1 litre of *Holzweg Wax Finish* will make up between 20 to 50 litres when mixed with warm water.
- Application** As a finishing treatment: Apply *Holzweg Wax Finish* undiluted with a damp cloth or mop evenly. When dry, polish.  
As a maintaining fluid: Mix approximately 200-500ml *Holzweg Wax Finish* into 10l of warm water. Apply with a damp cloth or mop. When dry, polish with a soft cloth.
- Drying times** Depending upon temperature and dampness polish after approximately 15 minutes.
- Storage** Container should be kept sealed, cool but frost free and out of the reach of children.
- Risk class** None.
- Ingredients** Carnauba wax, alcohol ester, water, sodium citrate

This technical information sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements. This sheet was issued on 18 November 2005 and may be superseded by later editions.