


# Construction Resources

## A QUICK GUIDE TO THE RANGE OF NATURAL PAINTS AND FINISHES QG1



Full Technical sheets are available on each product

---

### **MODERN NATURAL EMULSION PAINTS FOR WALLS AND CEILINGS**

*Natural Resin Emulsions are made almost entirely from tried and tested high quality natural raw materials. They look and act much like a conventional petrochemical emulsion and are just as easy to use, though they do not have the normal characteristic strong lingering smell of chemicals, are plastic free – reducing dust attraction, vapour permeable and biodegradable. They rely on linseed oil or natural latex not synthetic resins for their binding properties.*

#### **AQUAMARIJN MARIL MATT EMULSION: Class 2**

A brilliant white matt emulsion scrubbable to DIN 53778 (5000 cycles). Suitable for all internal walls and ceilings, including new and old plaster, brick, stone, woodchip/blown vinyl coverings, lining paper and most building boards. Used as the base for tinting with *Holzweg Pigments*. Hand made colour charts available. Completely solvent free, a pleasant natural odour, with a coverage up to 9 m<sup>2</sup> per litre. Supplied in 5 litre stainless steel tubs and 10 litre recycled plastic tubs.

#### **TIERRAFINO CLAY PAINT**

A clay based emulsion suitable for all internal walls and ceilings. It is available in seven base colours to match the Tierrafino through coloured clay plasters; Dover white, Delphi White, Roman Ochre, Djenne Red, Nassau Orange, Iquitos Green and Gomera Grey – these can all be mixed with each other to create a huge colour palette. Coverage 7m<sup>2</sup> per litre.

It is solvent free, antistatic, virtually non drip and has very good obliteration with a pleasing odour. Supplied in 5 and 10 litre containers.

#### **HOLZWEG EXTERNAL MASONRY PAINT (silicate paint):**

An exceptionally long lasting, brilliant white paint suitable for external masonry. The paint contains stabilised sodium silicate that enables the paint to bond chemically with its substrate. This results in a coating which is far less likely to flake, crack and ultimately fail. It comes in brilliant white though can be tinted with natural pigments mixed with *Holzweg Silicate Primer*. Coverage: approx. 7m<sup>2</sup> per litre. Supplied in 10 litre tubs (100% recyclable).

### **TRADITIONAL PAINTS FOR WALLS AND CEILINGS**

#### **HOLZWEG CASEIN WALL PAINT:**

This is a modern formulation of a traditional interior wall and ceiling paint, and makes for a unique, attractive and very affordable alternative to modern conventional petrochemical emulsion paint.

The paint is supplied in powder form and is mixed with cold water quickly and easily on site. It is made from nearly a dozen natural substances that make the use of the pigment titanium dioxide, solvents and preservatives obsolete. It is one of the most ecologically-sound paints we supply and gives very good vapour permeability and is washable after curing.

It can be applied in its natural white form or coloured with one or more pigments from our extensive range (coverage increases relative to pigment content). Recoatable after two hours it leaves the freshly painted room free of strong paint odours. Suitable for use in both authentic restoration and the modern home or office. Coverage: 8 – 10 m<sup>2</sup> per kilogram. Sizes: 4kg, 15kg, 25kg tough paper sacks. (1kg makes approx. 1 to 2 litres of paint).

## **PRIMERS FOR PLASTER, CONCRETE, ETC**

### **HOLZWEG SILICATE PRIMER: (water glass).**

A stabilising and priming solution for dusty and loose surfaces prior to painting or wallpapering, etc. Used as the grounding coat prior to *Holzweg External Emulsion* Coverage: 5 – 7 m<sup>2</sup> per litre depending on surface. Supplied in 5 and 10 litre containers.

## **NATURAL EARTH AND MINERAL PIGMENTS AND TINTS**

### **OCHRES, UMBERS, SIENNAS, ULTRAMARINES AND SPINELS**

There are 21 natural earth pigments and 15 mineral pigments in the Holzweg colour range, which come in dry powder form. Aquamarijn supply their pigment range pre-mixed in water to be used with the *Aquamarijn Maril emulsion colour tinting system*.

These pigments enable the decorator to create a whole spectrum of colours by mixing varying strengths of pigment with *Holzweg Casein Wallpaint*, *Holzweg Natural Resin Emulsion*, *Aquamarijn Maril Emulsion* or with *Holzweg Decorator's Glaze* to make up a transparent wash.

The pigments can also be used to tint various limewashes (except Ultramarine Blue/Violet). They have been selected for their excellent quality, have been washed and finely ground to ensure good colour distribution in any paint medium. Sizes: 75g paper sacks. Bulk quantities are available for extreme colours.

## **SPECIAL WALL FINISHES**

### **HOLZWEG TEXTURED WALL FINISH:**

A specially prepared powdered additive for *Holzweg Casein Wallpaint* containing sand and clay. When mixed into the paint it gives added texture to walls and ceilings. Textured casein wall paint makes an excellent base for various decorative effects such as 'Lasuur' (a form of multi-layered colour wash). Use 1 – 3kg of powder per 5 litres of paint. Supplied in 25kg tough paper sacks.

### **HOLZWEG COLOURWASH BINDER (wall varnish):**

*Holzweg Colourwash Binder* is used in the creation of colour wash effects for walls. Essentially a natural binder used to bind the pigment to the wall, it is diluted with water and mixed with the chosen pigment, and when dry the binder is colourless and virtually transparent. Used diluted with water the binder has a high spreadability. It can also be used untinted on *Holzweg Casein Wallpaint* as a type of 'wall varnish' to increase washability. Sizes 0.75, 2.5 litre tins.

## **HOLZWEG COLOURWASH CONCENTRATE:**

Based on the popular Holzweg Colourwash Binder, this concentrate is designed to make the application of colourwash effects even easier by pre mixing the binder and the most popular pigment colours into one. Just add water. Decorating with natural colours and materials has never been easier. Coverage depends on surface absorption. Supplied in 0.75 and 2.5 litre quantities to be added to water in a 1:1 ratio.

## **PRIMING OILS AND PAINTS FOR TIMBER AND METAL**

*Natural paints for timber are based on boiled linseed oil or stand oil - a higher grade linseed oil, both of which have excellent binding and levelling qualities i.e. the brush strokes settle back well. Technically, linseed oil takes years to fully harden leading to very long-lasting flexibility. Other ingredients include natural oils, resins and solvents such as genuine oil of turpentine. This results in flexible and deeply penetrating protective coatings that are biodegradable, vapour permeable (this helps to reduce the likelihood of paint film failure) and give the paints their characteristic and very pleasant smell.*

### **HOLZWEG LINSEED OIL:**

From organically grown flaxseed oil, suitable as a basic, first stage protection of all natural porous surfaces, such as timber, and terracotta tiles. It provides deep protection against water and dirt whilst still allowing the surface to breathe naturally. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

### **HOLZWEG HERBAL PRIMER:**

A standard wood priming oil for new and stripped interior timbers with low use. As with all Holzweg priming oils, the re-introduction of oils and resins from various trees and plants helps to condition and rejuvenate tired wood, repel insects and restrict fungal growth.

Suitable for use alone or under: *Holzweg Furniture Wax, Holzweg Antique Wax, Holzweg Varnish and Holzweg Lacquer/Marine Varnish*. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

### **HOLZWEG PRIMER:**

This primer is essentially *Holzweg Herbal Primer* but also contains wood stand oil and rizinene oil for greater protection for all new and stripped interior and exterior woodwork. Uses: as for *Holzweg Herbal Primer*, can also be used as a primer for Holzweg external varnishes such as *Holzweg UV Varnish, Walnut and Mahogany*, etc. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

### **HOLZWEG HARD OIL/ HARD OIL 'P':**

*Holzweg Hard Oil* contains added tung oil and coumarone resin. These extra ingredients make the oil tougher and provide added water and weather protection, making it suitable for heavily used porous surfaces such as floors, stairs, etc. It may be used on interior and exterior timber, cork, natural stone or terracotta tiles. Uses: as for *Holzweg Primer* can also be used under *Holzweg Hard Wax* on floors.

**Hard Oil 'P'**: the citrus solvent content is substituted with paraffin, which has a milder odour, mainly for professional use. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

### **AQUAMARIJN PRELIN WOOD PRIMER: Class 2**

(Opaque White) A professional, high quality linseed oil based wood primer for interior and exterior use. An excellent base prior to *Aquamarijn Linal Semi-Gloss* and *Holzweg White Undercoat*. Strong opaque white. Coverage approx. 10 – 12 m<sup>2</sup> per litre. Supplied in: 0.25, 0.75 2.5 and 5 litre tins.

### **AURO NATURAL METAL PRIMER No. 234:**

Opaque red primer for all interior and exterior applications. Suitable as basic corrosion protective treatment on uncoated rust free steel and metal. Coverage approx. 10 - 12 m<sup>2</sup> per litre. Sizes: 0.25, 0.75 and 2.5 litre tins.

### **AQUAMARIJN REVOL FLOOR/FURNITURE OIL: Class 1**

A quick drying, nourishing oil for all internal wood and absorbent stone. Helps to accentuate the grain of the substrate. Can be used alone or as priming treatment under *Aquamarijn Crelim Liquid Hard Conditioning Wax*. Coverage approx. 15 to 20m<sup>2</sup> per litre. Supplied in 1 and 5 litre and for special orders 10 litre tins.

### **AQUAMARIJN CORCOL CORK & TIMBER OIL: Class 1**

An interior floor oil for use on all untreated cork and absorbent wood such as pine or beech, etc. Being solvent free it is especially good for use in poorly ventilated areas. Use Revol for other types and situations. Can be used alone or, for best results, as a priming treatment under *Aquamarijn Crelim Liquid Hard Conditioning Wax*. Coverage approx. 20 m<sup>2</sup> per litre. Supplied in 1, 5 and for special orders 10 litre tins.

## **PAINT AND VARNISH FINISHES FOR TIMBER**

### **HOLZWEG WHITE UNDERCOAT:**

A flat wood paint to be used on top of *Aquamarijn Prelin Wood Primer* to make an excellent base for either *Holzweg Eggshell*, *Aquamarijn Satilin Eggshell* or *Holzweg Exterior Gloss*. Suitable for new and old woodwork, it dries quickly (touch dry in 3 hours, fully dry 8 hours) spreads easily and has good obliterating power. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.75, 2.5, 10 litre tins.

### **AQUAMARIJN LINAL UNDERCOAT/SEMI GLOSS: Class 2 or 3 depending on pigment used**

*Aquamarijn Linal* is a unique “single tin” painting system for all interior and exterior wood and metal work. The “one tin” system, i.e. an undercoat and top coat in one, makes painting easier by eliminating the need for extra paints. Linal has a slightly more silky/glossy sheen than *Aquamarijn Satilin Eggshell* and is available in 21 colours including brilliant white. (See colour chart).

The paint can also be used as an undercoat prior to *Aquamarijn Satilin* and *Aquamarijn Toplin*. The extended drying time helps achieve a superbly smooth and professional looking finish together with exceptionally long-lasting properties. Coverage approx. 10 – 12 m<sup>2</sup> per litre. Recoatable in 24 – 48 hours. Supplied in 0.25, 0.75, 2.5 and 5 litre tins (white only).

### **HOLZWEG WHITE EGGSHELL:**

This tough interior wood paint gives all woodwork a beautiful low sheen finish. It spreads easily and is touch dry within 3 hours and can be recoated within 8 hours (depending on conditions). It is tough and washable. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.75, 2.5, 10 litre tins.

### **HOLZWEG WHITE EXTERIOR GLOSS:**

For use on all exterior timber and metal. It dries quickly to leave a beautiful high gloss finish. It spreads easily and is fully washable. quickly (touch dry 3 hours, fully dry in 8 hours). Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.75, 2.5, 10 litre tins.

#### **AQUAMARIJN TOPLIN HIGH GLOSS: Class 4**

A beautiful high gloss paint for all interior and exterior timber and metal. This gloss achieves excellent colour and gloss retention ensuring long-lasting protection. Excellent flow characteristics with low propensity to run. It is the only Aquamarijn product with a Class 4 rating. Available in 10 colours including brilliant white. (See colour chart) . Use with *Holzweg Undercoat* or, for best results, use with *Aquamarijn Linal Undercoat/Semi Gloss*. Coverage 10 -12 m<sup>2</sup> per litre. Supplied in 0.75 and 2.5 litre tins.

#### **HOLZWEG VARNISH:**

Available clear or in a range of 8 colours. **Interior and exterior use** : WALNUT, LIGHT OAK, MAHOGANY, TEAK, PINE AND ULTRAMARINE BLUE. **Interior use only**: CLEAR, WHITE AND EBONY. For external clear varnish see *Holzweg UV Protection Varnish*. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

#### **HOLZWEG UV PROTECTION VARNISH:**

A special clear exterior wood varnish that gives long lasting protection from the sun's harmful ultra violet rays. Coverage 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

#### **HOLZWEG LACQUER**

An extremely durable full gloss clear lacquer suitable for interior woodwork. It is water-resistant and suitable for floors, stairs and other well-used surfaces. Coverage: 10 – 12m<sup>2</sup> per litre. Sizes: 0.125, 0.75, 2.5, 10 litre tins.

#### **AQUAMARIJN PLANC FLOOR VARNISHES: Class 3.**

An excellent answer to the problem of finishing timber flooring. It is a tough, flexible, washable and very durable clear varnish for use on wooden flooring and all other interior woodwork. Available in satin or full gloss sheen. Colour: clear. Coverage approx. 10 – 12 m<sup>2</sup> per litre. Supplied in 0.125, 0.75, 2.5 and 10 litres tins.

#### **AQUAMARIJN DRIERS:**

A natural mineral based drying additive for the *Satin* and *Gloss Planc Floor Varnish* to speed up drying times. Supplied in 0.03, 0.1, 0.5 and 5 litre tins.

### **FLOOR AND FURNITURE WAXES**

#### **AQUAMARIJN BALIM LIQUID WAX/OIL: Class 1**

An excellent, quick drying liquid wax/oil mix for all untreated cork and softwoods. Fills the pores to give good water and dirt resistance. Attractive clear satin finish with minimal change of base colour. Surface is useable within hours. Water diluteable and 100% solvent free. For best results finish *with Aquamarijn Crelim Liquid Hard Conditioning Wax*. Coverage approx. 12 – 20 m<sup>2</sup> per litre. Supplied in 0.75 and 2.5 litre tins.

#### **AQUAMARIJN CRELIM LIQUID HARD CONDITIONING WAX. Class 1**

Professional quick drying conditioning wax for care of both oil treated wood and existing wax finishes. Colourless and 100% solvent free, this wax contains an optimum combination of natural hard and nourishing waxes. Dirt and water resistant, with a beautiful satin finish. Water diluteable. Use with *Aquamarijn Balim Liquid Wax/Oil*, *Aquamarijn Corcol* or, for best results, *Aquamarijn Revol*. Coverage approx. 20 - 25 m<sup>2</sup> per litre. Supplied in 0.25, 1, 5, and, for special orders, 25 litre tins.

### **HOLZWEG FLOOR OIL:**

An extremely hardwearing professional 'all in one' oil, for heavily used timber floors. In many cases just one coat is required with no primer. A further 1 or 2 coats is recommended for commercial applications. Very high coverage (because no solvent is used) and "buff and walk" application make this product very economical in use. Coverage: 15 – 35m<sup>2</sup> per litre. Sizes: 0.75, 2.5, 10 litres.

### **HOLZWEG LIQUID PRESERVING WAX:**

A water-resistant wax oil for frequently used surfaces that have been pre-treated with either *Holzweg Hard Oil* and/or *Holzweg Primer*, especially wood and cork floors. When polished it gives the surface a beautiful silky sheen. Very easy to use. Coverage: 20 – 30m<sup>2</sup> per litre. Sizes: 0.75, 2.5, 10 litres.

### **HOLZWEG HARD WAX:**

Suitable for floors, stairs and other heavily used areas, it is a clear, water-resistant wax, which leaves a very hard surface in a beautiful light honey colour. Good for wood, cork or terracotta floors. Very economical to use. Coverage: 10 – 20m<sup>2</sup> per 0.4 litre tin. Size: 0.4 litre tin.

### **HOLZWEG FURNITURE WAX:**

A clear, water and dust repellent beeswax based product, which is ideal for the protection of all wood furniture. Coverage: 3 – 6m<sup>2</sup> per 0.25 litre tin. Size: 0.25 litre tin.

### **HOLZWEG ANTIQUE WAX:**

A hard furniture wax designed for restoration/colour matching work and available in mahogany, pine, teak, walnut and clear. The colours may be mixed together to match any particular wood. Coverage: 6 – 12m<sup>2</sup> per 0.5 litre tin. Sizes: 0.25, 0.5 litre tins.

## **EXTERIOR TIMBER CARE**

### **HOLZWEG EXTERIOR TIMBER PAINT:**

Supplied in Scandinavian Iron Oxide Red, this traditional paint is very much part of the northern landscape. It is boiled giving exceptionally long-lasting protection to your garden timber, weatherboarding, etc, while at the same time enhancing the local landscape with its beautiful rich colour. Coverage: 10 m<sup>2</sup> per litre. Sizes: 0.250 (sample), 5, 10 litres.

### **HOLZWEG FENCE PAINT:**

A long-lasting decorative wood preserver, suitable for all outdoor garden timber, supplied in a rich dark brown. It is water repellent and is not harmful to animals. Coverage: 10 m<sup>2</sup> per litre. Sizes: 0.125 (sample), 10 litres.

### **AQUAMARIJN EDELIN EXTERIOR STAIN: Class 2**

Professional stain for use on all interior and exterior windows and doors, etc. Supplied in 5 colours REDWOOD, SAPPHIRE BLUE, PINE, CLEAR, DARK OAK, and TEAK this high quality "one-can-system" protects and nourishes with its UV protection and essential oils. A water based product. Coverage approx. 10 – 12 m<sup>2</sup> per litre. Supplied in 0.250 (sample), 5, 10 litres.

### **AQUAMARIJN GARDOLIN: Class 1**

Professional impregnating linseed oil based stain for rough exterior garden timber. Totally safe to plants and animals. Matt finish. Available in a very attractive Moss Green colour. Coverage approx. 10 – 12 m<sup>2</sup> per litre. Supplied in 0.75 and 2.5 litre tins.

## **TIMBER PRESERVATION**

### **HOLZWEG TIMBER TREATMENT FLUID:**

One of the first natural treatments for existing woodworm and rot infestation. It is completely non toxic and safe for interior use. Tested by the Institute of Building in Switzerland, this treatment is guaranteed as an effective solution to insect and fungal damage. Coverage: Approx 10 m<sup>2</sup> per litre. Supplied in 0.75, 2.5 and 10 litre tins.

### **HOLZWEG BORON SALT:**

A transparent preservative for structural timbers, providing preventative protection against fungal and/or insect damage. It is one of the least toxic preservative available. Ideal for attic and roof timbers or timber where foodstuffs are stored. Not suitable for exterior woodwork. Supplied in powder form to be mixed with water. Coverage: 4 kg will protect 1 m<sup>3</sup> of timber. Sizes: 0.5, 2.5, 15 kilos.

## **PAINT STRIPPERS AND THINNERS**

### **HOLZWEG BALSAMIC TURPENTINE:**

An all purpose paint thinner and natural solvent, suitable for thinning *Holzweg Linseed Oil*, *Holzweg Primer*, *Holzweg Varnish*, *Holzweg Lacquer* and *Holzweg Hard Oil*. It can also be used to clean paint brushes, tools, and to remove grease from surfaces before painting, etc. Sizes 0.125, 0.75, 2.5, 10 litres.

### **HOLZWEG PAINT STRIPPER:**

A highly effective mixture of alkaline raw materials designed for the removal of old coats of oil, natural or synthetic paints (not suitable for epoxy resin paints). Supplied in powder form to be mixed with water. 1kg of stripper will strip approximately 1.5 m<sup>2</sup>. Sizes: 0.5, 2, 8, 14 kilos.

## **ADHESIVES**

### **HOLZWEG WALLPAPER PASTE:**

Suitable for hanging all types of wallpaper on absorbent or pre-treated surfaces. Completely free of fungicides, preservatives and synthetic resins, it is safe and easy to prepare and use. Supplied in powder form. 100g will hang up to 30m<sup>2</sup>. Sizes: 100 g and 0.5 kg bags.

### **HOLZWEG NATURAL LATEX FLOOR ADHESIVE:**

A natural resin and latex adhesive for gluing cork tiles, linoleum and carpet tiles onto porous and semi-porous floor and wall surfaces. Suitable for cement screeds or hardboard floors. Not suitable for epoxy resin screed. 1kg of floor adhesive will cover approximately 1.6m<sup>2</sup> of floor. Sizes: 2, 6, 16 kilogram tubs.

## **FLOOR MAINTENANCE**

### **HOLZWEG FLOOR MILK:**

An excellent all-purpose floor cleaner for maintaining sealed and waxed floors. Not only does it clean the floor it adds small amounts of wax as well thereby extending the life of the floor. Contains carnauba wax. 1 litre makes approximately 20- 40 litres when mixed with water. Sizes: 1, 5-litre bottles.

### **HOLZWEG FLOOR SOAP:**

A heavy-duty floor cleaner for stubborn dirt. Contains various natural oils to rejuvenate the floor as it cleans. 1 litre makes approximately 20- 40 litres when mixed with water. Sizes: 1, 5-litre bottles.

### **FILLERS FOR WOOD AND PLASTER**

#### **AQUAMARIJN PLAMUUR WOOD FILLER:**

Oil based filler for accurate filling of small imperfections in the timber surface. Supplied in 0.4 kg tubes.

### **MISCELLANEOUS HOME CARE**

#### **HOLZWEG HAND CLEANING PASTE:**

An all purpose heavy duty cleaning paste, suitable for workshops, garden or any job where dirt and grime is encountered. Harmless to skin and the environment. Size: 0.5 kilo paste

#### **HOLZWEG FURNITURE POLISH:**

A fragrant concentrate of plant extracts for the regular care and cleaning of oiled, waxed and sealed interior wood surfaces. Dissolves grease and dirt, leaving a silky sheen. Size: 0.25 litre.

#### **HOLZWEG SHOE POLISH:**

Available in brown and clear. Size: 0.75 kg.

#### **HOLZWEG LEATHER OIL:**

A traditional oil suitable for all leather materials. Its natural ingredients help restore and prolong tired and worn leather. Size: 0.75 litre.

This sheet is intended to provide guidelines for retailers and users. However, the user is responsible for testing the product on the intended surface to make sure that it is suitable for his or her requirements.

This 'Quick Guide to Construction Resources Natural Paints & Finishes' was issued on 30 May 2003 and may be superseded by later editions.

**CONSTRUCTION RESOURCES 1999**  
16 Great Guildford St, London SE1 0HS  
Tel: 0207 450 2211. Fax: 0207 450 2212.  
Email: [info@ecoconstruct.com](mailto:info@ecoconstruct.com)  
Web Site: [www.ecoconstruct.com](http://www.ecoconstruct.com)